

ALPHA[®] TRUEHEIGHT[®] SPACER

Tape & Reel Packaging / Spacer with Solderable Surface

DESCRIPTION

ALPHA TrueHeight Spacer is burr free, non-collapse copper discs coated with a barrier layer of nickel, and finish coated with flash gold. **ALPHA TrueHeight Spacer** is designed to be automatically placed and reflowed onto a printed circuit board pad printed with a nominal amount of solder paste. Since all sides of the spacer are coated, reflow does not result in exposed copper.

After reflow, the **ALPHA TrueHeight Spacer** provides a precise standoff height. Electronic components that are reflow soldered can benefit from the use of **ALPHA TrueHeight Spacer** to improve soldering results, such as to prevent corner signal shorting on large BGA devices with characteristic warping. Through hole components that need to be reflow soldered but do not contain sufficient standoff height can benefit from the use of **ALPHA TrueHeight Spacers**.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS


Features

- Non-collapse spacer function
- Nickel/ gold coated copper disc
- Burr free construction
- Excellent height dimensional tolerance – only $\pm 0.010\text{mm}$
- Fast placement utilizing standard pick and place equipment
- 7" standard IEC reels available

Benefits

- Burr free construction ensures repeatable height after reflow
- Nickel/ gold plating ensures no exposed copper after reflow
- Gold coating ensures highly solderable surface
- Tape and reel packaging for easy integration into standard assembly processes
- Excellent pick and place performance

PRODUCT INFORMATION

Part Dimensions

Part Type mm	Part Type inch	a		b	
		mm	inch	mm	inch
DS-D076H010	DS-D030H004	0.76	0.030	0.10	0.004
DS-D076H025	DS-D030H010	0.76	0.030	0.25	0.010
DS-D076H030	DS-D030H012	0.76	0.030	0.30	0.012
DS-D076H038	DS-D030H015	0.76	0.030	0.38	0.015

Tolerances on the part dimensions: $\pm 0.05\text{mm}$ for Dim. a; $\pm 0.010\text{mm}$ for Dim.

Contact your local sales representative for other available sizes

APPLICATION GUIDELINES

ALPHA TrueHeight Spacer are used to maintain a fixed height off the printed circuit board for electronic components. For components such as Ball Grid Array packages, excessive warping during reflow soldering can result in the corner signals shorting against each other as the “frowning” component corners come in near direct contact with the PCB. By adding spacers on the corners of the device, a minimum height is maintained, thus preventing signal shorting.


In applications such as reflow soldering of through hole components, adequate clearance between component body and PCB must be maintained to ensure clearance for solder paste print or preforms placed into the paste to add solder volume. If a through hole component does not have adequate clearance off the PCB, **ALPHA TrueHeight Spacer** can be added to the PCB to enable reflow soldering. This will reduce processing costs (eliminate wave soldering) and improve performance (increase hole fill).

TECHNICAL DATA

Alloy Information

All ALPHA TrueHeight Spacer is constructed of copper with nickel/gold finish.

Tape and Reel Packaging Information



Part Type mm	Tape Dimensions		
	W	P0	P1
	mm	mm	mm
DS-D076H030	8	4	2
DS-D076H038	8	4	2

SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available at AlphaAssembly.com**

STORAGE

The parts are packaged in ESD safe reels.

CONTACT INFORMATION

To confirm this document is the most recent version, please contact
Assembly@MacDermidAlpha.com
www.macdermidalpha.com

North America 300 Atrium Drive Somerset, NJ 08873, USA 800.367.5460	Europe Unit 2, Genesis Business Park Albert Drive Woking, Surrey, GU21 5RW, UK 01483.758400	Asia 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100
---	--	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.